



PP150LM – 71032840

Modular POS System



  **Android & Windows**

PP150LM R-71032840 Details

SPECIFICATION	ANDROID	WINDOWS
Processors	RK3568 4 x Cortex-A55 up to 2.0GHz RK3588 4 x Cortex-A76 + 4 x Cortex-A55 up to 2.2GHz RK3576 4 x Cortex-A72 + 4 x Cortex-A53 up to 2.2GHz DDR4 4GB On Board (Max. 8GB) 64GB Built-in eMMC (Max. 128GB) Android 11.0 (RK3568)/Android 12.0 (RK3588)/Android 14.0 (RK3576)	Intel® N97 (6M Cache, up to 3.60 GHz) Intel® Core™ i3-1215U(10M Cache, up to 4.40 GHz) Intel® Core™ i5-1235U(12M Cache, up to 4.40 GHz) 8GB Standard, DDR4 3200MHz(Max.32GB) 256GB Standard, M.22280 D2-M(Max. 1TB) Windows 10/Windows 11/Linux
Memory	DDR4 4GB on Board (Max. 8GB)	8GB Standard, DDR4 3200MHz(Max.32GB) 256GB
Storage	64GB Built-in eMMC (Max. 128GB)	256GB Standard, M.22280 D2-M(Max. 1TB)
Operating Systems	Android 11.0 (RK3568)/Android 12.0 (RK3588)/Android 14.0 (RK3576)	Windows 10/Windows 11/Linux
LCD	15" TFT LCD/15.6" FHD IPS LCD /18.5" FHD IPS LCD/21.5" FHD IPS LCD	
Resolution	1024x768(15")/1920x1080(15.6")/1920x1080(18.5")/1920x1080(21.5")	
Brightness	350 cd/m2(15")/250 cd/m2(15.6")/280 cd/m2(18.5")/300 cd/m2(21.5")	
Touch	10-points Projected Capacitive Touch	
Customer Display	VFD, 20 Columns x 2 Lines, 9.7" 2nd display(1024x768), 11.6" 2nd display(1920x1080), 15" 2nd display(1024x768), 15.6" 2nd display (1920x1080), Optional Touchscreen	
Port	8 USB, 1 HDMI, 1 lan (optional dual lan), 2 com port, 1 cr port, 3.5 mm audio jack, 1 power supply.	
Peripherals	RFID Reader(USB), 2D Barcode Scanner(USB), Fingerprint Reader(USB), Dallas i-Button Reader(USB), Magnetic Stripe Reader(USB,Support 1&2&3 Track)	
Wall Mount & Pole Mount	VESA-Compatible, Support both 75 x 75 (mm) and 100 x 100 (mm)	
Speaker	2 x 2W(Stereo)	
WiFi / BT	802.11a/b/g/n/ac, 802.11 ax optional/BT4.0	

BUILD YOUR POS WITH **MODULES**



Screen Module

+



System Box Module

=



POS


Screen Module



15"



15.6"



18.5"



21.5"

System Box Module



Windows Box Module

Intel® N97 (6M Cache, up to 3.60 GHz) Intel® Core™ i3-1215U(10M Cache, up to 4.40 GHz) Intel® Core™ i5-1235U(12M Cache, up to 4.40 GHz)



Android Box Module

RK3568 4 x Cortex-A55 up to 2.0GHz
RK3588 4 x Cortex-A76 + 4 x Cortex-A55 up to 2.2GHz
RK3576 4 x Cortex-A72 + 4 x Cortex-A53 up to 2.2GHz



Touch Monitor Box Module

HDMI + VGA

POS Peripheral Module



DESIGNED WITH **VERSATILITY** IN MIND



POSIO

Website : www.posio.in
Email : sales@posio.in

Address: 2 , MayureshDelta Tower 3,
Plot No.1 , Ulwe, Navi Mumbai